



Wafer and lugged options

HIGH PERFORMANCE BUTTERFLY VALVE
PTFE seat
ASME B16.5 150 and 300 LB
Firesafe Certified, Manual or Actuated
-40 to 250 Deg C
80mm to 600mm 150lb
80mm to 450mm 300lb



FLANGED WAFER BUTTERFLY
EPDM seat
AS/NZ AS4087 PN 16 **PN25 and PN40**
Gearbox operated
300mm to 1200mm
Now from 40mm to 2500mm options



CAST IRON BODY
FBE Coated
316 SS Disc
410 SS Shaft
EPDM seat
Gear or Lever operated
40mm to 300mm Rated 1600Kpa
350mm to 1200mm Rated 1000Kpa
Suit AS2129 D/E and ASME B16.5



CAST IRON BODY
FBE Coated
316 Disc
410 SS Shaft
EPDM seat
Gear or Lever operated
50mm to 300mm Rated 1600Kpa
350mm to 600mm Rated 1000Kpa
Suit AS2129 E Only



CAST IRON BODY
FBE Coated
316 SS Disc 410 SS Shaft
Viton seat
Gear or Lever operated
50mm to 300mm Rated 1600Kpa
350mm to 600mm Rated 1000Kpa
Suit AS2129 D/E and ASME B16.5



DUCTILE IRON BODY
FBE Coated
316 SS Disc
316 SS Shaft
NBR seat
Gear or Lever operated
40mm to 300mm Rated 1600Kpa
350mm to 600mm Rated 1000Kpa
Suit AS2129 E Only



CAST IRON BODY
FBE Coated
316 SS Disc
410 SS Shaft
NBR seat
Gear or Lever operated
50mm to 300mm Rated 1600Kpa
350mm to 600mm Rated 1000Kpa
Suit AS2129 D/E and ASME B16.5



CAST IRON BODY
FBE Coated
316 SS Disc
EPDM seat
410 SS Shaft
50mm to 300mm rated 1600Kpa
350mm to 600mm rated 1000Kpa
Suit ASME B16.5
Class 150 Only



CAST IRON BODY
FBE Coated
CI DISC PTFE COATED
316 SS Shaft
PTFE seat
Gear or Lever operated
50mm to 300mm Rated 1000Kpa
Suit AS2129 D/E and ASME B16.5



CAST IRON BODY
FBE Coated
CF8M SS Disc
NBR seat
ISO Pad 410 SS Shaft
Threaded Holes
50mm to 300mm rated 1600Kpa
350mm to 600mm rated 1000Kpa
Suit ASME B16.5
Class 150 Only



316 BODY
316 SS Shaft
SS DISC PTFE COATED
PTFE seat
Gear or Lever operated
50mm to 300mm Rated 1000Kpa
Suit AS2129 D/E and ASME B16.5



CAST IRON BODY
FBE Coated
CI DISC PTFE COATED
316 SS Shaft
PTFE seat
Gear or Lever operated
50mm to 300mm Rated 1000Kpa
Suit AS2129 E Only



316 BODY
316 Disc
316 SS Shaft
EPDM seat
Gear or Lever operated
50mm to 300mm Rated 1600Kpa
350mm to 600mm Rated 1000Kpa
Suit AS2129 D/E and ASME B16.5



316 BODY
316 Disc
316 SS Shaft
EPDM seat
Gear or Lever operated
50mm to 300mm Rated 1600Kpa
350mm to 600mm Rated 1000Kpa
Suit AS2129 E Only

Also refer WM and AGA approved versions