



**VALVE AND FLOW CONTROL SPECIALISTS**  
*SERVICE AND RELIABILITY*

**BUTTERFLY VALVE – CF8M Stainless Steel Body PTFE LINER  
Slim coated PTFE Disc**

FIGURE NO. VBY-WAETL

**End Type:** Wafer AS 2129 Table D / E ANSI 150

**Max Operating pressure:** 10 Bar

**Size range:** 50nb – 300NB Lever op Gear op option  
above 100nb

Ideal for Chlorinated water, salt water & waste water and  
general chemical service.



NO	PART NAME	MATERIAL
1	BODY	CF8M
2	DISC	PTFE COATED SS
3	STEM	316 SS
4	SEAT	PTFE
5	O-RING	NBR (NITRILE)

SIZE	K	J	H	Z	L	LOCATING HOLES TO SUIT PCD		D1	N	d4	D4	W	S	ISO	WEIGHT (kg)	
						TABLE D/E	ANSI 150								LEVER	GEAR
50	161	80	43	12.5	32	114	120.5	52.5	65	7	50	36	9	F05	4.5	-
65	175	89	46	12.5	32	127	139.5	63.8	65	7	50	36	9	F05	6.5	-
80	181	95	46	14.5	32	146	152.5	78.1	65	7	50	36	9	F05	7.5	13
100	200	114	52	16.5	32	178	190.5	103.8	90	9	70	56	11	F07	10	16
125	213	127	56	18.5	32	210	216	123.1	90	9	70	56	14	F07	12	18
150	226	139	56	18.5	32	235	241.5	155	90	9	70	56	14	F07	15	21
200	260	175	60	22.5	40	292	298.5	202.1	125	11	102	71	17	F10	23	33
250	292	203	68	30.5	40	356	362	250.1	125	11	102	71	22	F10	30	45
300	337	242	78	30.5	40	406	432	301.1	125	11	102	71	22	F10	43	59

