



VALVE AND FLOW CONTROL SPECIALISTS
SERVICE AND RELIABILITY

Miscellaneous Brass and Stainless Steel Fittings

This supplementary page is an addendum to the Arita Pipe Fittings and DK-Lok Instrumentation Fittings.

Recessed Allen Key Short Pattern Hex Plugs



Sizes 1/8" to 1" (6nb to 25nb)

Bodies Brass and 316 Stainless Steel

Application Marine/Hydraulic/Gas/Steam/Vehicular/ Industrial for blanking off valve / manifold/ regulators / hose or as drain plugs.

Pressure Range Brass 500psi (PT/NPT) Stainless 3000psi (PT/NPT).

End connections: P= Parallel (BSP) Thread, PT = parallel (BSP) taper Thread and NPT.

These are the short pattern versions compact design ie short threads. For higher pressure ratings up to 7000psi the standard or long pattern give full thread engagement. Refer the DK-Lok data for those (pic lower above).

Part No	Thread Size	Dimensions mm	Allen HEX Key
	P-PT-NPT	Length	
RHP-3N-S	1/8"	7	5
RHP-6N-S	1/4"	9	6
RHP-10N-S	3/8"	10	8
RHP-15N-S	1/2"	12	10
RHP-20N-S	3/4"	14	12
RHP-25N-S	1"	18	17

Part ordering References - Examples

RHP = Recessed Hex Plug

-3 etc relates to the thread size column 1/8"

N is for NPT, for BSP threads P is for parallel (straight) and PT is parallel tapered.

-S is for Stainless -B is for Brass

Details are current at time of publication
 and could vary with manufacturing
 enhancements subject to change without notice

VALVE AND FLOW CONTROL SPECIALISTS

E-mail sales@valveandflowcontrolspecialists.com