

VALVE AND CONTROL SPECIALISTS

STEAM INJECTORS - Series VSI

DESCRIPTION

The VSI series steam injectors are injection condensers. They ensure low noise and vibration with rapid heating of still or flowing fluids in basins and vessels due to direct steam injection. Steam enters through the inlet housing, passes along the center of the heater, through holes in the inner rings, via spaces between the element plates. Here it condensates under light load and partly condensates under heavy load to be discharged through the serrated periphery of the element plates. Under heavy load if any steam pass through the periphery of the element plates, will do so in very small jets and will condensate in the surrounding liquid with very little noise and vibration.

Connections are female screwed.

FEATURES

Quiet operation.

Corrosion-resistant.

No moving parts.

OPTIONS:

Complete system including

vacuum breaker and self operated controller. Different capacities and design available under request.


USE:

Direct steam injection heating systems. See IMI installation and maintenance instruction MODELS: VSI-4; VSI-5,5; VSI-7; VSI-8,5

SIZES: 3/4". MATERIAL OF CONSTRUCTION: AISI 304SS CONNECTIONS: Female screwed ISO 7/1 Rp (BS21) INSTALLATION: Horizontal or vertical installation. LIMITING CONDITIONS:

PMO: Max. operating pressure 8,5 bar TMO: Max. operating temperature 180°C How to order: i.e. VSI-4 DN 3/4" BSP

The pressure rating is stamped on the inlet housing. The VSI injector is made in one size and if one device does not pass sufficient steam, two or more should be fitted to a common supply pipe.



Example : We require to inject 950 Kg/hr of steam with a pressure of 5 bar. Assuming 20% pressure drop across the control valve, therefore the steam supply to the injectors will be 4 bar. From the injector capacity chart we see that the 4 bar injector will pass 293 Kg/hr and 950 divided by 293=3,24.

Three injectors of this size will barely cope, so we recommend installing four injectors, which will meet the demand.

