

## <u>VALVE AND FLOW CONTROL SPECIALISTS</u> SERVICE AND RELIABILITY

## **Brass Inline Poppet Check Valve** Figure VCP-B16N

A compact light industrial / HVAC inline non return valve that allows flow in one direction only for pipework in horizontal or vertical applications. This is a spring assisted closure valve, soft seated with solid brass valve member.

Size Range: 15mm through 80mm


PN 16 Non shock Cold Working Pressure

Max Working temp 80 Deg C

Pipe threads to BSP ISO

MATERIALS	
Body	Brass
Plunger	Brass
Spring	SS304
Seal	NBR





## **DIMENSIONS MM**

DN SIZE (mm)	A (mm)	C (mm)	D (mm)	WEIGHT (kg)
15	58	36	18	0.17
20	65	42	23	0.25
25	74.5	47	29	0.32
32	82	59.5	36	0.48
40	93	66.5	42.5	0.62
50	100	83	53.5	0.98
65	93	95	66	1.38
80	100	110	79	1.93
100	112	143	99	3.34

Also available in 304 and 316 Stainless Steel

Uncontrolled document subject to change without notice

Melbourne Sydney Brisbane Darwin Perth VALVE AND FLOW CONTROL SPECIALISTS E-mail sales@valveandflowcontrolspecialists.com