



VALVE AND FLOW CONTROL SPECIALISTS
SERVICE AND RELIABILITY

Namur Solenoid Valve For Spring Return Actuators




Figure NSOL-A-3/2

A 3 way 2 position solenoid valve with Namur interface make these suitable for direct mounting onto pneumatic SPRING RETURN ACTUATORS ONLY

(For Double acting refer NSOL-A-5/2)

Standard features include manual override, led indicator plug (IP65), fully encapsulated low wattage coil (AC 5.5 VA, DC 4.8 Watts). Available in all voltages.

Comes with mounting screws and O ring seal. Threads conform to ISO 7.1



A standard 3/2 solenoid bolts directly to the actuator no interface or conversion plates required.

Size Range: ¼” (Other sizes 3/8 and ½”)

Pipe threads to BSP

1.5 to 8 Bar Sol / Spring

5mm Orifice

CV 1.4

SC.A1

Class F Insulation

Media – Air not to exceed 70 Deg C

Din plug standard. Flying leads optional

Item	Material
Body	Aluminium
Spool	Aluminium
Operator	Stainless Steel
Seals	NBR
Ends	POM

Exhaust speed controllers, and silencers / protectors are available in Brass and Stainless steel and highly recommended to protect ingress of dust / external atmosphere etc.

High flow filter regulators should also be used in pneumatic systems or FRL's on larger systems to protect instrument air quality – also available.

Uncontrolled VCS document subject to change without notice

Lu June 2026

Melbourne Sydney Brisbane Darwin Perth
VALVE AND FLOW CONTROL SPECIALISTS
 E-mail sales@valveandflowcontrolspecialists.com